

DS-PWA32-KS

Wireless Kit

DS-PWA32-HS (433MHz, White) * 1
 DS-PD2-P10P-W (433MHz) * 1
 DS-PD1-MC-WWS (433MHz) * 1
 DS-19K00-Y (433MHz) * 1



DS-PWA32-HS (433MHz)

Model	DS-PWA32-HS
Wireless Inputs	32
Wireless Outputs	32
Users	12
Wireless Keyfob	8
Available RF Frequencies	Two-way wireless 433MHz
Wireless Siren	Max 2
Audio Output	1ch Audio Output
Status LEDs	5: 1 Orange (Fault), 2 Green (Power, Cloud connect), 1 Red (Alarm), 1 Blue (Arming)
Tamper Protection	Front and rear tamper protection
Control via Smart device	Hik-Connect (available on both iOS and Android)
Panel Assist By	Voice prompt
On Board Video Verification	Two channel (each channel 5s pre-event video and 2s after-event video)
Multi Languages Optional	English, French, Russian, Italian, Spanish, Portuguese (upgrade via Cloud)
Ethernet	10/100 Mbps Self-Adaptive Ethernet
3G/4G	Supports Report Push-Notification to CMS, Cloud; Text notification via SMS; Audio notification via phone call (Model: -HS, -HSR)
SIM Card Slot	1 (Models: -HG, -HS, -HGR, -HSR)

Reset	1
Wi-Fi Protocol Standard	802.11b/g/n
Wi-Fi Security Encryption	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Hik SDK Protocol Compatible	Supports Hik-SDK, management on iVMS-4200
Ezviz Protocol Compatible	Supports Ezviz Protocol, management on Hik-Connect
ARC Communication	SIA-Contact ID
Web Server	For configuration via web browser
Mobile App	Supports Alarm Push-Notification, Arming/Disarming, Status Checking, Report Checking, Video Linkage
Onvif Protocol	Supports third party IPC integration
Power Supply	Included 5VDC, 10W
Power Consumption	<5.6W
Backup Battery	1 Lithium battery, 3.8V, 4520mAh (Battery life up to 12 hours)
Operating Temperature	-10°C to 55°C
Operating Conditions	10% to 90% (Non-Condensing)
Dimensions (W x H x D)	155 x 155 x 35mm
Colour	White
Shell Material	PC+ABS

DS-PD2-P10P-W (433MHz)

Model	DS-PD2-P10P-W
Detection Range	10m, detection angle: 85°
Detection Speed	0.3m/s ~ 3.0m/s
Transmission Range	800m in open space
Animal Immunity	Up to 24kg
Transmission frequency	433MHz
Power Supply	1×CR123A, 3.0V, 2 years Battery life
Operation Temperature	-10°C ~ +40°C
Dimension(L*W*H)	117mm*69mm*50mm
Weight	125g
Installation Environment	Indoor
Installation Height	1.8m ~ 2.4m

DS-PD1-MC-WWS (433MHz)

Model	DS-PD1-MC-WWS
-------	---------------

Transmitting frequency	433MHz
RF Transmission distance	800m (Open area)
LED indicator	1
Tamper switch	Supported
Power interface	CR123A 3.0V, 2 years
Operation temperature	-10°C~+55°C
Operation humidity	10%~90%
Dimension(L x W x H)	84mm x 25mm x 20.99mm
Weight	37 g

DS-19K00-Y (433MHz)

Model	DS-19K00-Y
Button	Arm, Disarm, Stay arm, Panic alarm, Alarm elimination
Frequency	433MHz
Distance	300m (Open area)
Encryption Scheme	Rolling code DES
Indicator	Red/Green LED
Battery	3V/210mAh
Size (L x W x H)	63mm x 49mm x 16mm
Weight	24.5